



# The Solution for Your Needs

## How to choose your ball valves?

### Which kind of valve do you need ?

• **Ball Valves**



• **Needle Valves**



• **Butterfly Valves**



Represents an interesting economical alternative compared with a ball valve

• **Axial Valves**



### What are the conditions of use ?

- Pressure
- Temperature inside the system
- Sealing requirements
- Flow requirements
- 2 ways or 3 ways
- Normally closed / Normally open ?

### What type of fluid is being conveyed ?

- Compatibility of materials with the fluid : body & seals

### Which technology is required to connect your ball valves ?

- Compression
- Threaded
- Push-in connection

### Have you considered the additional product requirements ?

- Compression fittings
- Tubing
- Solenoid valves

### What is your application environment ?

- Internal or external environment
- Risk of shocks
- Air quality
- Regulations
- Corrosion risk
- Frequency of operation

### What other functions are required ?

- Lockable
- Vented
- Frequency of operation
- Electric or pneumatic

## Part Number Identification

**0402 04 10**

Valve type

0400  
0401  
0402  
...















O.D. tube

04 = 4 mm  
05 = 5 mm  
...  
40 = 40 mm

Thread

10 = 1/8"  
13 = 1/4"  
...  
48 = 2"

# Product Specifications Overview

	Materials	Fluids	Maximum Pressure (bar)	Temperature		Page
				Min.	Max.	
<b>Industrial Valves</b>						
<b>Universal and Customised Series Ball Valves</b> 	Nickel-plated forged brass	Compressed air Other fluids (see compatibility chart)	40	-40°C	+80°C +100°C: please contact us	<b>444</b>
<b>Universal Series, Vented</b> 	Nickel-plated forged brass	Compressed air Other fluids (see compatibility chart)	40	-20°C up to -40°C with no handle operation	+80°C	<b>447</b>
<b>Universal Series, Lockable</b> 	Nickel-plated forged brass, galvanised steel and epoxy locking system	Compressed air Other fluids (see compatibility chart)	40	-40°C	+80°C	<b>448</b>
<b>Universal Light Series</b> 	Forged brass or nickel-plated forged brass	Compressed air Other fluids (see compatibility chart)	20	-20°C	+80°C	<b>449</b>
<b>DVGW Series Ball Valves</b> 	Nickel-plated brass	Compressed air Other fluids (see compatibility chart)	40	-40°C	+170°C	<b>451</b>
<b>Standard Series Ball Valves</b> 	Nickel or chromium plated brass	Compressed air Other fluids (see compatibility chart)	30	-20°C	+130°C	<b>452</b>
<b>Stainless Steel Series Ball Valves</b> 	Stainless steel 316L	All fluids	35	-20°C	+150°C	<b>454</b>
<b>High Pressure Ball Valves</b> 	Zinc-plated brass	Compressed air, lubricants, gases	300	-15°C	+80°C	<b>456</b>
<b>Mini Series Ball Valves</b> 	Technical polymer/ Nickel-plated brass	Compressed air	10	-20°C	+80°C	<b>457</b>
<b>LIQUIfit® Ball Valves</b> 	Polypropylene	Beverages, water, industrial water, CO <sub>2</sub> , inert gases	10	-15°C	+100°C	<b>459</b>
<b>Brass Needle Ball Valves</b> 	Shot-blasted forged brass nickel-plated	Compressed air, water, industrial fluids Other fluids: please contact us	120	-20°C	+100°C	<b>461</b>
<b>Stainless Steel Needle Valves</b> 	Stainless steel 316L	All fluids	400	-20°C	+180°C	<b>460</b>
<b>Butterfly Valves</b> 	Shot-blasted forged brass nickel-plated	Compressed air, abrasive fluids	16	-20°C	+80°C	<b>462</b>
<b>Axial Valves</b> 	Nickel-plated brass	Compressed air, water, industrial fluids Other fluids: please contact us	10	-20°C	+135°C	<b>463</b>

# Compatibility Table

The chart below shows the compatibility between valves and fluids along with their pressure and temperature characteristics.

Certain models have a maximum working pressure which differs from that given in this table. In this case, the pressure is shown in the heading for the model number in question.

N.B.: Above 32 mm or 1¼" diameters, divide the maximum pressure by 2.

If the fluid you are using is not shown in this chart, please contact us.

Chemical Description	Maximum Pressure (bar)	Temperature °C		Universal and Light Series	Standard Series	DVGW series
		Min.	Max.			
"Aromatic" hydrocarbons	20	-20	+60			
Acetone and other ketones	20	-20	+60			
Acetophenone	20	-20	+60			
Acetylene - Acetone	20	-20	+60			
Acetylene (gas)	20	-20	+60	●	●	●
Alcohol (100%)	20	-20	Boiling			
Aluminium (liquid suspension, thick)	40	-20	+90	●	●	●
Amyl alcohol	20	-20	Boiling			
Animal fats, greases	20	+5	+200		●	●
Antifreeze or glycol (diluted)	40	-20	+40	●	●	●
Argon (gas) Ar	20	-20	+60	●	●	●
Barium - Hydroxide	20	-20	+40			
Benzaldehyde	20	-20	+60			
Benzene	20	-20	+60			
Benzyl alcohol	20	-20	Boiling			
Borax (pastes or solutions)	20	-20	+60			
Brake fluids (automobile)	20	-20	+90			
Bromochlorotrifluoroethane	20	-20	+60		●	●
Butadiene (hydrocarbon)	20	-20	+60			
Butane	20	-20	+60	●	●	●
Butanol	20	-20	Boiling			
Butyl alcohol	20	-20	Boiling			
Butylene (hydrocarbon)	20	-20	+60			
Carbon dioxide gas CO <sub>2</sub>	40	-20	+60	●	●	
Castor oil	40	-20	+90	●	●	
Compressed air	20	-25	+180	●	●	●
Creosotes	20	-20	+60			
Cresols	20	-20	+60			
Crude oil	20	-20	+40			
Cutting oil	40	-20	+90	●	●	
Decalin (hydrocarbon, solvent)	20	-20	+60			
Detergents (solutions)	20	-20	+100			
Diacetone alcohol	20	-20	Boiling			
Diesel oils	40	-20	+90	●	●	
Di-Esters	20	-20	+90			
Di-Isobutylene	20	-20	+60			
Di-Pentane	20	-20	+60			

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.

# Compatibility Table

Chemical Description	Max. Pressure (bar)	Temperature °C		Universal and Light Series	Standard Series	DVGW Series
		Min.	Max.			
Di-Pentene (solvents, varnish)	20	-20	+60			
Di-Phenyl-Oxide (thin detergents)	20	-20	+60			
Distilled water	40		+90	●	●	●
Edible fats	20	+5	+200		●	
Edible oils	20	+5	+200		●	
Erytrene (see Butadiene)	20	-20	+60			
Ethane (gas) CH <sub>2</sub> CH <sub>3</sub>	20	-20	+60	●	●	
Ethane (hydrocarbon gas)	20	-20	+60			
Ethyl alcohol	20	-20	+60			
Ethylene glycol (antifreeze) - see Glycols	20	-20	+120			
Fatty alcohols	20	-20	Boiling			
Fuel oils	40	-20	+40	●	●	●
Fuels-Diesels	40	-20	+40	●	●	
Gaseous oxygen (ambient air)	20	-20	+40			
Glycerine	20	-20	+40	●	●	
Glycol (for antifreeze, lubricants)	40	-20	+40	●	●	
Graphite in suspension in water, oils and greases	40	-20	+90	●	●	
Greases (from petroleum)	40	-20	+90	●	●	
Helium (gas)	20	-20	+60			
Heptanal	20	-20	+50	●	●	
Hexane (solvent)	20	-20	+60			
Hydraulic oils (petroleum-based)	40	-20	+90	●	●	
Hydrogen (gas)	20	-20	+60			
Inks	20	-20	+60			
Insecticides	20	0	+40	●	●	●
Iso-Butane (aliphatic hydrocarbon)	20	-20	+60			
Iso-Octane	20	-20	+60			
Isopropyl alcohol	20	-20	Boiling			
Krypton (gas) Kr	20	-20	+60	●	●	●
Light water	40		+80	●	●	●
Lighting gas	20	-20	+40			●
Methane (gas) CH <sub>4</sub>	20	-20	+60	●	●	●
Methanol	20	-20	Boiling			
Methyl alcohol	20	-20	Boiling			
Methylated spirit	40	-20	+40	●	●	●
Mineral oils	40	-20	+90	●	●	●
Natural gas	20	-20	+40			●
Natural waxes (vegetable, beeswax, carnauba, Chinese, lignite)	40	-20	+90			
Neatsfoot oil	40	-20	+90	●	●	●
Neon (Gas) Ne	20	-20	+60	●	●	●
Nitrogen (gas) N <sup>2</sup>	40	-20	+90	●	●	●
Oil (petroleum-based) and water emulsions	40	-20	+90	●	●	●

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.

# Compatibility Table

Chemical Description	Max. Pressure (bar)	Temperature °C		Universal and Light Series	Standard Series	DVGW Series
		Min.	Max.			
Oils "synthetic"	20	-20	+100			
Ordinary petrol	20	-20	+40	●	●	
Oxygenated water	40	-20	+30			
Paints and relevant solvents	20	-20	+60		●	●
Paraffin oil	40	-20	+90	●	●	●
Paraffins	20	-20	+60	●	●	●
Pentane (liquid hydrocarbon)	20	-20	+60	●	●	●
Pentanol 1 and 2	20	-20	Boiling			
Petrol "super"	20	-20	+40			
Petroleum mineral oils	20	-20	+160			
Phenol (aqueous or alcoholic)	20	-20	+60		●	●
Propane	20	-20	+60	●	●	●
Propanol 1 and 2	20	-20	Boiling			
Propanone 2	20	-20	+60			
Propene or Propylene	20	-20	+60			
Propyl alcohol	20	-20	Boiling			
Propylene or Propene	20	-20	+60			
Rapeseed oil	40	-20	+90	●	●	
Saponifying liquids	20	-20	+30	●	●	●
Seawater	40		+80	●	●	●
Seawater (high temperature)	20		+150			●
Soaps	20	-20	+100			
Soaps (liquid or paste)	40	-20	+40	●	●	●
Sodium carbonate (with water)	20	0	+40	●	●	●
Starch (gels or pastes)	40	+10	+40	●	●	●
Steam	20	-20	+150			
Toluene (terpene hydrocarbon)	20	-20	+60		●	●
Trichlorethylene	20	-20	+65			
Turpentine	20	-20	+50	●	●	●
Varnish and paints	20	-20	+60		●	●
Vaseline	40	-20	+60	●	●	●
Vaseline oil	40	-20	+90	●	●	●
Water (carbonated)	40		+90	●	●	●
Water (high temperature)	20		+150			●
Xenon (gas) Xe	20	-20	+60	●	●	●
Xylene	20	-20	+60			

The above recommendations are given in good faith. However, since each application is different, it is advisable to undertake tests in actual working conditions.



# Universal Series



The seal wear compensating technology offers reliable and durable sealing, whether under pressure or vacuum.

## Technical Characteristics

- **Compatible Fluids:** Compressed air  
Other fluids: see compatibility chart at the end of this chapter
- **Working Pressure:** Vacuum up to 40 bar, depending on the model
- **Working Temperature:** -20°C to +80°C  
up to -40°C with no handle operation


Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.

Guaranteed for use with a vacuum of 755 mm Hg (99 % vacuum).

## Advantages

- Automatic seal wear compensation
- Vacuum resistance
- Ease of operation
- Short, repositionable and exchangeable handles

## Component Materials



## Regulations

- PED
- REACH
- RoHS

## Installation Options

### Lockable Valves

Our lockable ball valves have been developed in order to prevent potentially dangerous consequences caused by unintended operation. Lockable in different positions, this range meets international safety requirements, such as ISO 4414.

The valves are lockable:

- at one point: models 0432 and 0439, open or closed position
- at three points: models 0436, 0437 and 0438, closed position only

### Vented Valves

To stop fluid circulation and vent the circuit, 2 venting systems are provided:

- with threaded exhaust, to allow discharge of downstream media
- with pin-hole vent, for applications with no special discharge requirement

Fluid flow direction is indicated by an arrow on the valve body.

### Mountable Valves

On steel plate:


- bulkhead fixing
- complete valve below bulkhead

On frame:

- assemble with bolts


On wooden panel:

- assemble with woodscrews



## 0400 2/2 In-Line Ball Valve, Male BSPP Thread

Nickel-plated brass, NBR




DN	C	E	F	H	H1	J	L	L1	M	Kg	
4	G1/8	0400 04 10	7	14	35	29	14	45	25	48	0.094
7	G1/4	0400 07 13	9	19	38	31	19	60	36	48	0.166
10	G3/8	0400 10 17	11	24	45	43	24	70	43	69	0.252
13	G1/2	0400 13 21	12	27	47	44	27	78	45	69	0.324
18	G3/4	0400 18 27	12	38	63	54	39	90	50	108	0.714

Maximum working pressure: 40 bar

## 0411 2/2 In-Line Ball Valve with Connections for Use with Steel Tubing

Nickel-plated brass, NBR




DN	ØD	F	F1	H	H1	J	L	L1	M	Kg	
4	6	0411 04 06	14	19	38	31	19	76	30	48	0.173
6	8	0411 06 08	17	19	38	31	19	77	30	48	0.195
7	10	0411 07 10	19	19	38	31	19	78	31	48	0.210
10	12	0411 10 12	22	24	45	43	24	85	36	69	0.310

Maximum working pressure: 40 bar



## 0402 2/2 In-Line Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR




DN	C		E	F	F1	H	H1	L	L1	M	Kg
4	G1/8	<b>0402 04 10</b>	8	14	35	29	44	25	48	0.094	
7	G1/8	<b>0402 07 10</b>	8	19	19	38	31	51	27	48	0.165
	G1/4	<b>0402 07 13</b>	12	19	19	38	31	53	28	48	0.156
10	G3/8	<b>0402 10 17</b>	12	24	24	45	43	59	31	69	0.244
13	G1/2	<b>0402 13 21</b>	15	27	27	47	44	67	34	69	0.292
20	G3/4	<b>0402 20 27</b>	16.5	32	38	63	54	80	39	108	0.655
23	G1	<b>0402 23 34</b>	19	41	46	67	57	94	47	108	1.036
32	G1 1/4	<b>0402 32 42*</b>	21.5	55	60	97	115	112	59	180	2.467
	G1 1/2	<b>0402 32 49*</b>	22	55	60	97	115	120	62	180	2.340
40	G1 1/2	<b>0402 40 49*</b>	22	55	55	104		111	55	190	2.445
	G2	<b>0402 40 48*</b>	26	70	70	104		122	61	190	2.614

\*Models with EC marking  
Maximum working pressure: 40 bar

## 0401 2/2 In-Line Ball Valve, Male/Female BSPP Thread

Nickel-plated brass, NBR




DN	C		E	E1	F	H	H1	J	L	L1	M	Kg
4	G1/8	<b>0401 04 10</b>	8	7	14	35	29	14	45	25	48	0.094
5	G1/8	<b>0401 05 10</b>	8	7	19	38	31	19	51	27	48	0.160
7	G1/4	<b>0401 07 13</b>	12	9	19	38	31	19	52	28	48	0.150
10	G3/8	<b>0401 10 17</b>	12	11	24	45	43	24	58	31	69	0.234
13	G1/2	<b>0401 13 21</b>	15	12	27	47	44	27	66	34	69	0.286
18	G3/4	<b>0401 18 27</b>	16.5	12	38	63	54	39	79	39	108	0.652
23	G1	<b>0401 23 34</b>	19	15	46	67	57	48	91	47	108	0.952
32	G1 1/4	<b>0401 32 42*</b>	21.5	18	60	97	115	55	113	59	108	2.385

\*Models with EC marking  
Maximum working pressure: 40 bar

## 0446 2/2 In-Line Panel-Mountable Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR




DN	C		E	F	F1	H	H1	H2	L	L1	M	T	Kg
4	G1/8	<b>0446 04 10*</b>	8	14	22	37	14	12	44	25	48	16.5	0.112
7	G1/4	<b>0446 07 13</b>	12	19	24	45	19	14	53	28	48	20.5	0.188
10	G3/8	<b>0446 10 17</b>	12	24	24	50	21	21	59	31	69	20.5	0.294
13	G1/2	<b>0446 13 21</b>	15	27	24	51	23	21	67	34	69	20.5	0.338

Maximum working pressure: 20 bar  
\*For G1/8 version, maximum panel thickness = 3 mm

## 6402 2/2 In-Line Ball Valve for Screw Fixing, Female BSPP Thread

Nickel-plated brass, NBR




DN	C		E	F	F1	G	H1	H2	L	L1	M	N	T	Kg
4	G1/8	<b>6402 04 10</b>	8	14	14	18	18	30	44	25	48	25	470	0.132
7	G1/4	<b>6402 07 13</b>	12	19	19	19	24	31	53	28	48	31	580	0.216
10	G3/8	<b>6402 10 17</b>	12	24	24	20	30	45	59	31	69	31	580	0.324
13	G1/2	<b>6402 13 21</b>	15	27	27	20	34	47	67	34	69	34	6100	0.404
20	G3/4	<b>6402 20 27</b>	16.5	32	38	27	44	52	80	39	108	43	8125	0.830
23	G1	<b>6402 23 34</b>	19	41	46	27	53	56	94	47	108	51	8125	1.290

Maximum working pressure: 40 bar

## 6401 2/2 In-Line Ball Valve for Screw Fixing, Male/Female BSPP Thread

Nickel-plated brass, NBR




DN	C		E	E1	F	G	H1	H2	L	L1	M	N	T	Kg
4	G1/8	<b>6401 04 10</b>	8	7	14	18	18	30	45	25	48	25	470	0.127
7	G1/4	<b>6401 07 13</b>	12	9	19	19	24	31	52	28	48	31	580	0.212
10	G3/8	<b>6401 10 17</b>	12	11	24	20	30	45	58	31	69	31	580	0.306
13	G1/2	<b>6401 13 21</b>	15	12	27	20	34	47	67	34	69	34	6100	0.394

Maximum working pressure: 40 bar

## 0472 2/2 Right-Angled Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR




DN	C		E	F	H	H1	H2	J	L	L1	M	Kg
4	G1/8	<b>0472 04 10</b>	8	14	35	29	18	14	34	25	48	0.096
6	G1/4	<b>0472 06 13</b>	12	19	38	31	24	22	38	28	48	0.191
9	G3/8	<b>0472 09 17</b>	12	24	45	43	27	25	46	31	69	0.260
12	G1/2	<b>0472 12 21</b>	15	27	47	44	33	29	49	34	69	0.312
18	G3/4	<b>0472 18 27</b>	16.5	38	59	51	40	39	60	39	108	0.704
23	G1	<b>0472 23 34</b>	19	46	63	55	47	48	72	47	108	1.062

Maximum working pressure: 20 bar

## 0471 2/2 Right-Angled Ball Valve, Male/Female BSPP Thread

Nickel-plated brass, NBR




DN	C	E	E1	F	H	H1	H2	J	L	L1	M	Kg	
4	G1/8	0471 04 10	8	7	14	35	29	19	14	34	25	48	0.096
6	G1/8	0471 06 10	8	7	19	38	31	22	22	37	27	48	0.182
	G1/4	0471 06 13	12	9	19	38	31	25	22	38	28	48	0.187
9	G3/8	0471 09 17	12	11	24	45	43	28	25	46	31	69	0.256
12	G1/2	0471 12 21	15	12	27	47	44	32	29	49	34	69	0.303
18	G3/4	0471 18 27	16.5	12	38	59	51	37	39	60	39	108	0.682
23	G1	0471 23 34	19	15	46	63	55	44	48	72	47	108	1.020

Maximum working pressure: 20 bar


## 0482 3/3 Right-Angle Ported Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR




DN	C	E	F	H	H1	H2	J	L	L1	M	Kg	
4	G1/8	0482 04 10	8	14	35	29	18	14	44	25	48	0.102
6	G1/4	0482 06 13	12	19	38	31	24	22	53	28	48	0.200
9	G3/8	0482 09 17	12	24	45	43	27	25	59	31	69	0.284
12	G1/2	0482 12 21	15	27	47	44	33	29	67	34	69	0.346
18	G3/4	0482 18 27	16.5	38	59	51	40	39	80	39	108	0.742
23	G1	0482 23 34	19	46	63	55	47	48	94	47	108	1.160

Maximum working pressure: 20 bar




## 0483 3/3 Right-Angle Ported Ball Valve Without Closed Position, Female BSPP Thread

Nickel-plated brass, NBR




DN	C	E	F	H	H1	H2	J	L	L1	M	Kg	
4	G1/8	0483 04 10	8	14	35	29	18	14	44	25	48	0.102
6	G1/4	0483 06 13	12	19	38	31	24	22	53	28	48	0.196
9	G3/8	0483 09 17	12	24	45	43	27	25	59	31	69	0.278
12	G1/2	0483 12 21	15	27	47	44	33	29	67	34	69	0.340
18	G3/4	0483 18 27	16.5	38	59	51	40	39	80	39	108	0.716
23	G1	0483 23 34	19	46	63	55	47	48	94	47	108	1.066

Maximum working pressure: 20 bar



## 0448 3/3 Panel-Mountable Right-Angled Ball Valve, Female BSPP Thread


Nickel-plated brass, NBR



DN	C	E	F	F1	H	H1	H2	H3	J	L	L1	M	T	Kg	
4	G1/8	0448 04 10*	8	14	22	37	14	18	12	14	44	25	48	16.5	0.126
6	G1/4	0448 06 13	12	19	24	45	19	24	14	22	53	28	48	20.5	0.230
9	G3/8	0448 09 17	12	24	27	50	21	27	21	25	59	31	69	20.5	0.328
12	G1/2	0448 12 21	15	24	27	51	23	33	21	29	67	34	69	20.5	0.392


Maximum working pressure: 20 bar

\*For G1/8 version: maximum panel thickness = 3 mm




## 0452 3/2 Panel-Mountable Equal Plane Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR




DN	C	E	F	F1	H	H1	H2	J	K	L	T	Kg	
4	G1/8	0452 04 10	8	14	22	39	10	8	16	18	25	19	0.130
6	G1/4	0452 06 13	12	19	22	40	11	11	23	24	28	20	0.206

Maximum working pressure: 20 bar



## 0489 3/2 In-Line Threaded Exhaust Port Ball Valve, Female BSPP and Metric Thread

Nickel-plated brass, NBR




DN	C1	C	E	F	F1	H	H1	H2	L	L1	M	T	Kg	
7	M5x0.8	G1/4	0489 07 13	12	24	24	46	43	17	59	31	69	2	0.270
10	M5x0.8	G3/8	0489 10 17	12	24	24	46	43	17	59	31	69	2	0.243
13	G1/8	G1/2	0489 13 21	15	27	27	47	44	24	67	34	69	2	0.310
18	G1/4	G3/4	0489 18 27	16.5	32	38	63	54	33	80	39	108	2.5	0.670
23	G1/4	G1	0489 23 34	19	41	46	67	57	37	94	47	108	3	1.050

Maximum working pressure: 40 bar

## 0462 3/2 Right-Angled Ball Valve with Vent, Female BSPP Thread

Nickel-plated brass, NBR




DN	C	E	F	H	H1	H2	J	L	L1	M	Kg	
6	G1/8	0462 06 10	8	19	38	31	20	22	37	27	48	0.192
	G1/4	0462 06 13	12	19	38	31	24	22	38	28	48	0.185
9	G3/8	0462 09 17	12	24	45	43	27	25	46	31	69	0.261
12	G1/2	0462 12 21	15	27	47	44	33	29	49	34	69	0.311
18	G3/4	0462 18 27	16.5	38	59	51	40	39	60	39	108	0.698
23	G1	0462 23 34	19	46	63	55	47	48	72	47	108	1.066

Maximum working pressure: 20 bar

## 0449 3/2 Panel-Mountable In-Line Threaded Exhaust Port Ball Valve, Female BSPP and Metric Thread

Nickel-plated brass, NBR




DN	C1	C	E	F	F1	H	H1	H2	H3	L	L1	M	T	Kg	
7	M5x0.8	G1/4	0449 07 13	12	24	24	50	20	17	21	59	31	69	2.5	0.313
10	M5x0.8	G3/8	0449 10 17	12	24	24	50	20	17	21	59	31	69	2.5	0.291
13	G1/8	G1/2	0449 13 21	15	27	24	52	23	24	21	67	34	69	4	0.352

Maximum working pressure: 20 bar

## 0461 3/2 Right-Angled Ball Valve with Vent, Male/Female BSPP Thread

Nickel-plated brass, NBR




DN	C	E	E1	F	H	H1	H2	J	L	L1	M	Kg	
6	G1/8	0461 06 10	8	7	19	38	31	20	22	37	27	48	0.182
	G1/4	0461 06 13	12	9	19	38	31	24	22	38	28	48	0.186
9	G3/8	0461 09 17	12	11	24	45	43	27	25	46	31	69	0.257
12	G1/2	0461 12 21	15	12	27	47	44	33	29	49	34	69	0.304
18	G3/4	0461 18 27	16.5	12	38	59	51	40	39	60	39	108	0.648

Maximum working pressure: 20 bar

## 0469 3/2 In-Line Vented Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR




DN	C	E	F	F1	H	H1	L	L1	M	T	Kg	
4	G1/8	0469 04 10	8	14	14	35	29	44	25	48	1.5	0.092
7	G1/4	0469 07 13	12	24	24	46	43	59	31	70	2	0.268
10	G3/8	0469 10 17	12	24	24	46	43	59	31	70	2	0.246
13	G1/2	0469 13 21	15	27	27	47	44	67	34	70	2	0.294
18	G3/4	0469 18 27	16.5	32	38	63	54	80	39	108	2.5	0.668
23	G1	0469 23 34	19	41	46	67	57	94	47	108	3	1.026


Maximum working pressure: 40 bar

### Operation of Vented Ball Valves

With vent connected to a tube = collection of purged media





With vent connected to a silencer = noiseless discharge to atmosphere



## 0432 2/2 In-Line Lockable Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR





DN	C		E	F	F1	H	H1	L	L1	M	Kg
4	G1/8	0432 04 10	8	19	19	59	54	51	27	69	0.415
7	G1/4	0432 07 13	12	19	19	59	54	59	28	69	0.396
10	G3/8	0432 10 17	12	24	24	60	55	59	31	69	0.460
13	G1/2	0432 13 21	15	27	27	62	57	67	34	69	0.510
20	G3/4	0432 20 27	16.5	32	38	66	56	80	39	108	0.800
23	G1	0432 23 34	19	41	46	70	59	94	47	108	1.186

Maximum working pressure: 40 bar  
Handle is not removable.  
Fixed and mobile plates: zinc-plated steel.

## 0437 3/2 In-line Vented 3-Point Lockable Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR





DN	C		E	F	F1	H	L	L1	M	T	Kg
7	G1/4	0437 07 13	12	24	24	60	59	32	69.5	2	0.476
10	G3/8	0437 10 17	12	24	24	60	60	32	69.5	2	0.447
13	G1/2	0437 13 21	15	27	27	60	67.5	34.5	69.5	2	0.510
18	G3/4	0437 18 27	16.5	32	38	69.5	80	39.5	108.5	2.5	0.820
23	G1	0437 23 34	19	41	46	73	94.5	47.5	108.5	3	1.192

Maximum working pressure: 40 bar  
Handle is not removable  
Locking plates are zinc-plated steel

## 0439 3/2 In-line Vented Lockable Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR





DN	C		E	F	F1	H	H1	L	L1	M	T	Kg
4	G1/8	0439 04 10	8	19	19	59	54	51	27	69	2	0.410
7	G1/4	0439 07 13	12	24	24	60	55	59	31	69	2	0.480
10	G3/8	0439 10 17	12	24	24	60	55	59	31	69	2	0.460
13	G1/2	0439 13 21	15	27	27	62	57	67	34	69	2	0.514
18	G3/4	0439 18 27	16.5	32	38	66	56	80	39	108	2.5	0.810
23	G1	0439 23 34	19	41	46	70	59	94	47	108	3	1.185

Maximum working pressure: 40 bar  
Handle is not removable, locking plates are zinc-plated steel.

## 0438 3/2 Right-Angled 3-Point Lockable Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR





DN	C		E	F	H	H1	J	L	L1	Kg
9	G3/8	0438 09 17	12	38	76	34	39	73	35	0.970
12	G1/2	0438 12 21	15	38	76	37	39	78	38	0.947
18	G3/4	0438 18 27	16.5	38	76	40	39	80	40	0.905
23	G1	0438 23 34	19	46	80	47	48	94	47	1.295

Maximum working pressure: 20 bar  
Fixed plate: zinc-plated steel, mobile plate: zinc-plated steel  
Removable handle: where the handle is obstructed in its movement, it can be refitted opposite the original position.

## 0436 3/2 In-Line 3-Point Lockable Ball Valve with Threaded Exhaust Port, Female BSPP and Metric Thread

Nickel-plated brass, NBR



DN	C1	C		E	F	F1	H	H1	L	L1	M	Kg
10	M5x0.8	G3/8	0436 10 17	12	24	24	60	17	60	32	69	0.475
13	G1/8	G1/2	0436 13 21	15	27	27	60	24.5	67.5	34.5	69	0.500
18	G1/4	G3/4	0436 18 27	16.5	32	38	69.5	33	80	39.5	108	0.850
23	G1/4	G1	0436 23 34	19	41	46	73.5	47.5	94.5	47.5	108.5	1.215

Maximum working pressure: 40 bar  
Handle is not removable.  
Fixed and mobile plates: zinc-plated steel

# Universal Light Series



Suitable for small, compact and resistant spaces, these ball valves are easy to operate.

## Technical Characteristics

- **Compatible Fluids:** Industrial fluids
- **Working Pressure:** Vacuum to 12 bar
- **Working Temperature:** -20°C to +80°C

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.

Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).

## Advantages


- Compactness
- Corrosion resistance due to chemical nickel plating
- Automatic compensation of seal wear
- Repositionable and exchangeable handles

## Regulations

- PED
- REACH
- RoHS

## Component Materials

### Silicone-free



## 0492 2/2 In-Line Ball Valve, Female BSPP Thread

Nickel-plated brass, NBR



DN	C		E	F	H	L	L1	M	Kg
4	G1/4	0492 04 13	9	17	34	39.5	17	35	0.073
7	G3/8	0492 07 17	11	22	38	45	20	43	0.128
10	G1/2	0492 10 21	12	24	44	54	25	50	0.150
13	G3/4	0492 13 27	14	30	46	62	28	50	0.240

Technical polymer handle

## 0491 2/2 In-Line Ball Valve, Male/Female BSPP Thread

Nickel-plated brass, NBR




DN	C		E	E1	F	H	L	L1	M	Kg
4	G1/4	0491 04 13	9	7	17	34	39.5	17	35	0.070
7	G3/8	0491 07 17	11	8	22	38	45	20	43	0.124
10	G1/2	0491 10 21	12	10	24	44	53	24	50	0.160
13	G3/4	0491 13 27	14	12	30	46	59	25	50	0.238

Technical polymer handle

## 0492..64 2/2 In-Line Ball Valve, Short Handle, Female BSPP Thread

Nickel-plated brass, NBR




DN	C		E	F	H	L	L1	M	Kg
4	G1/4	0492 04 13 64	9	17	36	39.5	17	25	0.090

Short handle in zamak

## 0491..64 2/2 In-Line Ball Valve, Short Handle, Male/Female BSPP Thread

Nickel-plated brass, NBR




DN	C		E	E1	F	H	L	L1	M	Kg
4	G1/4	0491 04 13 64	9	7	17	36	39.5	17	25	0.092

Short handle in zamak

## 0490 2/2 In-Line Ball Valve, Male BSPP Thread

Nickel-plated brass, NBR




DN	C		E	F	H	L	L1	M	Kg
4	G1/4	0490 04 13	7	17	34	39	17	35	0.070
7	G3/8	0490 07 17	8	22	38	44	20	43	0.109
10	G1/2	0490 10 21	10	24	44	53	24	50	0.160
13	G3/4	0490 13 27	12	30	46	59	25	50	0.233

Technical polymer handle

## 0497 2/2 Ball Valve, Square Stem, Female BSPP Thread


Brass, NBR



DN	C		E	F	H	J	L	L1	Kg
4	G1/4	0497 04 13	9	17	25	7	39	17	0.063
7	G3/8	0497 07 17	11	22	26	7	45	20	0.122
10	G1/2	0497 10 21	12	24	29	10	54	25	0.141
13	G3/4	0497 13 27	14	30	30	10	62	28	0.230

## 0496 2/2 Ball Valve, Square Stem, Male/Female BSPP Thread

Brass, NBR



DN	C		E	E1	F	H	J	L	L1	Kg
4	G1/4	0496 04 13	7	9	17	25	7	39	17	0.065
7	G3/8	0496 07 17	8	11	22	26	7	45	20	0.118
10	G1/2	0496 10 21	10	12	24	29	10	53	24	0.150
13	G3/4	0496 13 27	12	14	30	30	10	59	28	0.222



Compliant with DVGW certification, standardized threads, these valves ensure the transport of gas and water.

## Technical Characteristics

- **Compatible Fluids:** Compressed air, water, gas
- **Working Pressure:** 1/4" to 2": 0 to 40 bar
- **Working Temperature:** -50°C to +170°C

Reliable performance is dependent upon the type of fluid conveyed.


Products have been tested at -50°C in static sealing and after 5 operations for a leak rate < 0,05NI/h.

## Advantages


- Stem prevented from being ejected in the event of overpressure
- Two stem seal to prevent leakage
- Corrosion resistance, increased chemical compatibility thanks to chemical nickel plating
- Can be operated at very low temperatures: -50°C

## Working Pressure and Temperature

Pressure - Temperature



Pressure Drop



## Regulations


**Industrial**  
**DI: 97/23/EC**  
**(PED B+D module EC 1115)**

**Water**  
**DVGW: W 570-1**  
**DIN EN 13228**  
**BGA KTW**  
**DVGW: W270**

**Gas**  
**DIN EN 33**

## BVG4-L 2/2 In-Line Ball Valve, Female BSPP Thread


Nickel-plated brass



DN	C		E	F	G	H	L	M	Kg
8	G1/4	BVG4-1/4L	12	17	25	38	50	82	0.150
10	G3/8	BVG4-3/8L	12	20	25	38	60	82	0.161
15	G1/2	BVG4-1/2L	15.5	25	32.5	43	75	100	0.256
20	G3/4	BVG4-3/4L	17	32	39	50	80	120	0.397
25	G1	BVG4-1L	21	41	47.5	54	90	120	0.641
32	G1 1/4	BVG4-1.1/4L	23	50	59	73	110	158	0.980
40	G1 1/2	BVG4-1.1/2L	23	55	71.5	79	120	158	1.205
50	G2	BVG4-2L	26.5	70	86	86	140	158	1.960

## BVGT4-L 2/2 In-Line Ball Valve, Female BSPP Thread, Butterfly Handle

Nickel-plated brass



DN	C		E	F	G	H	L	M	Kg
8	G1/4	BVGT4-1/4L	12	17	25	39	50	50	0.137
10	G3/8	BVGT4-3/8L	12	20	25	39	60	50	0.129
15	G1/2	BVGT4-1/2L	15.5	25	32.5	43	75	50	0.231
20	G3/4	BVGT4-3/4L	17	32	39	47	80	60	0.348
25	G1	BVGT4-1L	21	41	47.5	51	90	60	0.546

Compact lever

# Standard Series



For common industrial applications, these ball valves are equipped with fluoropolymer seals and a lockable system.

Technical Characteristics		
Model	Standard and Lockable Series	Compact Series
Compatible Fluids	Compressed air Other fluids : see compatibility chart at the end of this chapter	
Working Pressure	0 to 40 bar up to 2" 0 to 30 bar over 2" excepted BVG4P-LOCK and BVG4-LOCK: 0 to 14 bar	0 to 30 bar
Working Temperature	-20°C to +170°C Excepted BVG4P-LOCK: -10°C to +100°C	-10°C to +90°C

Reliable performance is dependent upon the type of fluid conveyed.

- ### Advantages
- Long or butterfly handle
  - Full fluid flow
  - A lockable version for safety in use
  - Corrosion resistance thanks to chemical nickel plating

### Component Materials

**Silicone-free**

Long lever: Geomet® plated steel  
Compact Series lever: technical polymer  
Butterfly lever: Aluminium

Locking system: treated steel  
Stem seal: FPM o-rings  
Locking nut and Locking screw: Zinc plated steel

Stem: nickel-plated brass

Body: nickel-plated or chromium-plated shot-blasted brass


Seat seals: PTFE  
Ball: chromium-plated brass

4902 (G2-G4), BVGT-C, BVG4-LOCK: Double stem seal: FPM

- ### Regulations
- Industrial:
- PED
  - REACH
  - RoHS

## 4902 2/2 Standard In-Line Ball Valve, Female BSPP Thread

Nickel-plated brass, PTFE




DN	C		E	F	H	L	M	PN	Kg
8	G1/4	4902 10 13	9	17	38	39	82	40	0.131
10	G/8	4902 10 17	9	20	38	39	82	40	0.117
15	G1/2	4902 15 21	11	25	43	50	100	40	0.204
20	G3/4	4902 20 27	12	31	50	54	120	40	0.329
25	G1	4902 25 34	14	38	54	67	120	40	0.468
32	G1 1/4	4902 32 42*	15	48	73	77	158	30	0.770
40	G1 1/2	4902 40 49*	17	54	79	90	158	30	1.040
50	G2	4902 50 48*	19	66	86	106	158	30	1.760
65	G2 1/2	4902 65 47*	22	85	132	136	255	30	4.500
80	G3	4902 80 46*	25	99	140	157	255	30	5.840
100	G4	4902 01 45*	29	125	154	191	255	30	9.040

\*Models with EC marking  
Model from 2 1/2": double stem seal in FPM  
Working temperature: -20°C to +170°C

## 4991 2/2 Standard Compact In-Line Ball Valve, Male/Female BSPP Thread


Chromium brass, PTFE



DN	C		E	E1	F	H	L	L1	M	Kg
6	G1/8	4991 00 10	10	10	21	30	41.5	10	24	0.089
8	G1/4	4991 00 13	11	11	21	30	41.5	11	24	0.082
	G3/8	4991 00 17	11	11	21	30	41.5	10.5	24	0.087
10	G1/2	4991 00 21	13	13	25	32	49	12.5	24	0.134

## 4992 2/2 Standard Compact In-Line Ball Valve, Female BSPP Thread

Chromium brass, PTFE









DN	C		E	F	H	L	L1	M	Kg
6	G1/8	4992 00 10	10	21	30	41.5	10	24	0.111
8	G1/4	4992 00 13	11	21	30	41.5	11	24	0.100
	G3/8	4992 00 17	11	21	30	41.5	10.5	24	0.094
10	G1/2	4992 00 21	13	25	32	49	12.5	24	0.142



## BVGT4-C 2/2 Standard In-Line Ball Valve, Female BSPP Thread, Butterfly Handle

Nickel-plated brass









DN	C		E	F	G	H	L	M	Kg
8	G1/4		9	17	25	40	39	50	0.130
10	G3/8		9	20	25	40	39	50	0.120
15	G1/2		11	25	32.5	44	50	50	0.180
20	G3/4		12	31	39	49	54	50	0.265
25	G1		14	38	47.5	53	67	50	0.390

Compact lever

## BVG4-LOCK 2/2 In-Line Lockable Ball Valve, Female BSPP Thread

Nickel-plated brass




DN	C		E	F	H	L	M	Kg
8	G1/4		9	17	46	39	96	0.150
10	G3/8		9	20	46	39	96	0.150
15	G1/2		11	25	51	50	96	0.255
19	G3/4		12	31	59	54	117	0.390
25	G1		14	38	63	67	117	0.590






Double stem seal in FPM

Working temperature -40°C to +170°C

## BVG4P-LOCK 3/2 In-Line Lockable Vented Ball Valve, Female BSPP Thread

Nickel-plated brass



DN	C		E	F	H	L	L1	M	Kg
8	G1/4		12	17	47.5	45	22.5	96	0.155
10	G3/8		12	20	47.5	45	22.5	96	0.172
15	G1/2		15.5	25	52	59	29.5	96	0.239
20	G3/4		17	31	59.5	64	32	117	0.371
25	G1		21	40	63.5	81	40.5	117	0.581

Working pressure: 14 bar

Working temperature: -10°C to +100°C

# Stainless Steel Series



For severe food or industrial process applications, a series with a 316L stainless steel body that withstands aggressive environments, as well as high pressures and temperatures.

## Technical Characteristics

Compatible Fluids	Types 4810, 4812 and 4832	Type 0465
	All fluids	All fluids
Working Pressure	0 to 65 bar (see details in product tables below)	Vacuum to 20 bar
Working Temperature	-20°C to +150°C	-20°C to +120°C


Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.

Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).

## Advantages

- Chemical compatibility
- High temperature operation: up to +150°C
- 3 straight versions :
  - Compact type cannot be disassembled
  - 3-piece can be disassembled
  - Light series for more compactness

## Component Materials




## Regulations


- Industrial:
- PED
  - REACH
  - RoHS

## Pressure and Temperature Resistance

### Version 4810, 4812 and 4832




### Version 0465



## 4832 2/2 In-Line 3-Piece Ball Valve with Fixing Plate, Female BSPP Thread

Stainless steel 316L, PTFE




DN	C	NP	E	F	G	H	K	L	M	T	Kg	
10	Rp1/4	4832 10 13**	64	18	22	36	50	36	57	110.5	5.5	0.272
15	Rp1/2	4832 15 21	64	20.5	27	36	64	36	65	131.5	6	0.478
20	Rp3/4	4832 20 27	40	22.5	32	42	68	42	76	131.5	5.5	0.568
25	Rp1	4832 25 34	40	27	41	42	78.5	42	92	174.5	6	1.229
32	Rp1 1/4	4832 32 42*	25	30	50	42	83.5	42	106.5	174.5	5.5	1.530
40	Rp1 1/2	4832 40 49*	25	31	55	50	100	50	116	250.5	6.5	2.146
50	Rp2	4832 50 48*	25	36	70	50	107	50	136	250.5	6.5	3.140

\*Models with EC marking \*\*  
 Without Fixing Plate  
 Threads conformed to ISO 7/1

## 4812 2/2 In-Line Ball Valve with Fixing Plate, Female BSPP Thread

Stainless steel 316L, PTFE




DN	C	NP	E	G	H	L	M	T	Kg	
10	Rp1/4	4812 10 13	140	10	36	50	55	110	5.5	0.263
	Rp3/8	4812 10 17	140	11	36	50	55	110	5.5	0.254
15	Rp1/2	4812 15 21	140	15	36	53	66	110	5.5	0.336
20	Rp3/4	4812 20 27	105	16	42	67	79	130	5.5	0.574
25	Rp1	4812 25 34	105	19	42	79	93	175	5.5	1.010
32	Rp1 1/4	4812 32 42*	64	21	42	83	100	175	5.5	1.337
40	Rp1 1/2	4812 40 49*	64	21	50	100	110	250	6.5	2.161
50	Rp2	4812 50 48*	64	26	70	107	131	250	6.5	3.262

\*Models with EC marking  
 Threads conformed to ISO 7/1

## 4810 2/2 In-Line Ball Valve, Female BSPP Thread

Stainless steel 316L, PTFE




DN	C		E	G	H	L	M	Kg
8	G1/4	<b>4810 08 13</b>	10	30	44.5	53.5	110.5	0.206
10	G3/8	<b>4810 10 17</b>	10	30	44.5	53.5	110.5	0.190
15	G1/2	<b>4810 15 21</b>	13	32.5	47	60	110.5	0.245
20	G3/4	<b>4810 20 27</b>	14	40	54.5	70	131.5	0.418
25	G1	<b>4810 25 34</b>	17	49	58.5	79	131.5	0.648

Threads conformed to ISO 228/1-G

## 0465 2/2 In-Line Light Series Ball Valve, Female BSPP Thread

Stainless steel 303, PTFE



DN	C		E	F	F1	H	L	Kg
4	G1/4	<b>0465 04 13</b>	13	19	24	36	50	0.226
7	G3/8	<b>0465 07 17</b>	13	24	27	39	55	0.278
10	G1/2	<b>0465 10 21</b>	16	27	30	40	62	0.322

Silicone-free

Threads conformed to ISO 228/1-G

# High Pressure Series



Designed for applications up to 300 bar, these carefully manufactured ball valves guarantee safe operation.

## Technical Characteristics

- **Compatible Fluids:** Compressed air, lubricants, gases
- **Working Pressure:** Vacuum to 300 bar
- **Working Temperature:** -15°C to +80°C

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.


Guaranteed for use with a vacuum of 755 mm Hg (99% vacuum).

## Advantages

- Low operating torque, even at high pressure
- Repositionable and exchangeable handles
- Robust design resistant to high tightening torques
- Fixing screws for through-bulkhead mounting

## Component Materials

### Silicone-free




## Regulations

- PED
- REACH
- RoHS

## Installation Options


### Bulkhead Mounting

Through bulkhead with screws




### Surface Mounting

With brackets and screws



## 4402 2/2 In-Line High Pressure Ball Valve, Female BSP Thread

Treated brass, NBR



DN	C	E	H1	H2	H3	J	K	L	L1	N	N1	Kg
7	G1/4	4402 07 13	12	50	13	15	30	30	58	25	15	0.402
10	G3/8	4402 10 17	12	54	23	19	36	39	72	36	20	0.722
13	G1/2	4402 13 21	15	56	23	21	40	42	79	36	20	0.870

# Mini Series



Equipped with push-in connections and a technical polymer body, this series combines lightness on the equipment, speed of installation.

## Technical Characteristics

- **Compatible Fluids:** Compressed air, neutral gases
- **Working Pressure:** Vacuum to 10 bar
- **Working Temperature:** -20°C to +80°C

Tightening Torques	Threads	G1/8	G1/4	G3/8	G1/2
	daN.m	0.8	1.2	3	3.5

Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.


Guaranteed for use with a vacuum of 755 mm Hg (99 % vacuum).

## Advantages

- Lightweight and compact
- LF 3000® push-in connections, static and dynamic sealing
- Automatic seal wear compensation for long-term reliability
- Ultra-compact handle, easy operation, screwdriver slot for difficult access

## Component Materials


### Silicone-free



## Installation Options


### Vented Valve, Open Position

3/2 model with vent




### Vented Valve, Closed Position

Lever with screwdriver slot



## 7910 2/2 In-Line Mini-Ball Valve


Technical polymer, NBR



ØD		G	H	H1	K	L	N	Kg
4	7910 04 00	15	37	7.5	22	51	16	0.039
6	7910 06 00	15	37	7.5	22	52	16	0.034
8	7910 08 00	15	37	7.5	22	52	16	0.025
10	7910 10 00	20	43	11	30	66	22	0.060
12	7910 12 00	20	43	11	30	66	22	0.040

## 7911 2/2 In-Line Mini-Ball Valve, Male BSPP Thread


Technical polymer, Nickel-plated brass, NBR



ØD	C		E	F	G	H	K	L	L1	N	Kg
6	G1/8	7911 06 10	5	13	14	37	22	62	37	16	0.045
8	G1/4	7911 08 13	5.5	16	17.5	37	22	61	35	16	0.040
10	G3/8	7911 10 17	5.5	20	22	43	30	74	41	22	0.075
12	G1/2	7911 12 21	7.5	24	26	43	30	75	42	22	0.075

## 7913 3/2 In-Line Mini-Ball Valve with Vent


Technical polymer, NBR



ØD		G	H	H1	K	L	N	Kg
4	7913 04 00	15	37	7.5	22	51	16	0.040
6	7913 06 00	15	37	7.5	22	52	16	0.035
8	7913 08 00	15	37	7.5	22	52	16	0.025
10	7913 10 00	20	43	11	30	66	22	0.060
12	7913 12 00	20	43	11	30	66	22	0.045

## 7914 3/2 In-Line Mini-Ball Valve with Vent, Male BSPP Thread

Technical polymer, Nickel-plated brass, NBR



ØD	C		E	F	G	H	K	L	L1	N	Kg
6	G1/8	7914 06 10	5	13	14	37	22	62	37	16	0.045
8	G1/4	7914 08 13	5.5	16	17.5	37	22	61	35	16	0.040
10	G3/8	7914 10 17	5.5	20	22	43	30	74	41	22	0.058
12	G1/2	7914 12 21	7.5	24	26	43	30	75	42	22	0.075

## 7000 Joining Clips

Technical polymer



ØD		Kg
4	7000 00 04	0.001
6-8	7000 00 05	0.005
10-12	7000 00 06	0.001

## Complementary Products for Mini Series

LF 3000®

PA Tubing

PU Tubing

Flow Regulators





As an integral part of the LIQUIfit® range, these ball valves are designed for water and beverage handling circuits. FDA, NSF and WQA standards are a guarantee of safety for the health of consumers. These ball valves offer sealing and cleanliness to the equipment.

## Technical Characteristics

- **Compatible Fluids:** Water, drinks, beverages, industrial water, CO<sub>2</sub>, inert gases
- **Working Pressure:** 0 to 10 bar at 20°C
- **Working Temperature:** -15°C to +100°C


## Advantages

- Technical polymer body
- Full flow self-sealing ball maintains the cleanliness of the circuit
- LIQUIfit® push-in connection, static and dynamic sealing. No pumping effect. Resistant to water hammer.

## Regulations


- **FDA: 21 CFR**
- **NSF 51**

## Component Materials



## 4020 2/2 In-Line Ball Valve

Polypropylene with fibreglass, EPDM




ØD			H	H1	L	L1	Kg
6	4020 06 00WP2		36	13	57	27	0.019
8	4020 08 00WP2		36	13	60	27	0.020
10	4020 10 00WP2		36	13	70	33	0.023
12	4020 12 00WP2		36.5	13	88	43	0.034

## 4020 2/2 In-Line Ball Valve

Inch

Polypropylene with fibreglass, EPDM




ØD			H	H1	L	L1	Kg
1/4	4020 56 00WP2		36	13	57	27	0.015
3/8	4020 60 00WP2		36	13	70	33	0.028

## 4021 2/2 In-Line Ball Valve, Male NPTF Thread

Inch

Polypropylene with fibreglass, EPDM




ØD	C		H	H1	L	L1	Kg
1/4	NPTF1/4	4021 56 14WP2	36	13	61	31	0.029
3/8	NPTF3/8	4021 60 18WP2	36	13	64	33.5	0.028

## 4023 2/2 In-Line Ball Valve, Female NPTF Thread

Inch

Polypropylene with fibreglass, EPDM




ØD	C		H	H1	L	L1	Kg
3/8	NPTF3/8	4023 60 18WP2	36	13	64	33.5	0.028

## 4022 2/2 Right-Angled Ball Valve, Female NPTF Thread

Inch

Polypropylene with fibreglass, EPDM



ØD	C		H	H1	L	L1	Kg
1/4	NPTF1/4	4022 56 14WP2	52	29	44	31	0.016

## 4024 2/2 Right-Angled Ball Valve

Polypropylene with fibreglass, EPDM



ØD			H	H1	L	L1	Kg
6	4024 06 00WP2		54	31	41	27	0.020
10	4024 10 00WP2		61	38	47	33	0.024

# Needle Valves



Made of nickel-plated brass or stainless steel, the needle valves are designed for applications that require manual flow adjustment.

## Technical Characteristics

	Brass	Stainless Steel
Compatible Fluids	Compressed air, water, industrial fluids, etc. Other fluids: contact us	Many fluids
Working Pressure	0 to 120 bar	0 to 400 bar
Working Temperature	-20°C to +100°C (except model 0510)	-20°C to +180°C


Reliable performance is dependent upon the type of fluid conveyed.

## Advantages

- Manual flow adjustment
- Numerous valve and safety accessory configurations

## Component Materials

### Silicone-free




## Regulations

- PED
- REACH
- RoHS

## 0502 In-Line Needle Valve, Female BSP Thread


Nickel-plated brass



DN	C	Part No.	E	H	H max	J	L/2	Kg
4	G1/8	0502 04 10	9	56	50	17	23	0.133
	G1/4	0502 04 13	11	56	50	17	23	0.120
6	G3/8	0502 06 17	12	67	60	26	0.171	
9	G3/8	0502 09 17	12	82	70	33	0.426	

## 0510 In-Line Needle Valve with Compression Connections

Nickel-plated brass




DN	ØD	C	Part No.	F	H min	H max	L/2	Kg
4	6	M10x1	0510 04 06	13	42	46	29	0.083
8	8	M12x1	0510 05 08	14	42	46	30	0.083
5	10	M16x1.5	0510 05 10	19	42	46	31	0.134

The needle is sealed by an O-ring.  
Maximum operating pressure: Ø4: 100 bar, Ø5: 60 bar  
Working temperature: -15°C to +70°C  
Tightening torques: please refer to the Compression Fittings chapter of this catalogue.

## 0501 In-Line Needle Valve, Male/Female BSP Thread


Nickel-plated brass



DN	C	Part No.	E	E1	H	H max	J	L	Kg
4	G1/8	0501 04 10	9	7	56	50	17	44	0.118
	G1/4	0501 04 13	11	9.5	56	50	17	46	0.115
6	G3/8	0501 06 17	12	9.5	67	60	48	0.158	

## 0532 Right-Angle Needle Valve, Female BSP Thread

Nickel-plated brass




DN	C	Part No.	E	H min	H max	H1	J	L	Kg
4	G1/8	0532 04 10	9	46	52	46	19	17	0.093
	G1/4	0532 04 13	11	46	52	46	21	17	0.087
6	G1/4	0532 06 13	11	55	63	55	26	22	0.171



## 0531 Right-Angle Needle Valve, Male/Female BSP Thread

Nickel-plated brass



DN	C	E	E1	H min	H max	H1	J	L	Kg	
4	G1/8 0531 04 10	7	9	46	52	46	19	17	19	0.082
	G1/4 0531 04 13	9.5	11	46	52	46	21	17	21	0.090
6	G1/4 0531 06 13	9.5	11	55	63	55	25	22	26	0.155
	G3/8 0531 06 17	9.5	12	55	63	55	25	22	27	0.153
10	G1/2 0531 10 21	13	16	62	72	62	34	26	33	0.329

## 0562 Needle Drain Valve, Male BSP and Metric Thread

Brass



DN	C	E	F	H min	H max	Kg
5	G1/8 0562 05 10	8	16	36	40	0.032
	G1/4 0562 05 13	10	19	38.5	42.5	0.040
	M10x1 0562 05 60	8	16	37.5	40	0.031

## 0563 Needle Drain Valve, BSPT Thread


Brass



DN	C	F	H min	H max	Kg
5	R1/4 0563 05 14	14	28.5	32.5	0.021

## 0627 Automatic Vent Pressure Gauge Valve, Female BSP Thread

Nickel-plated brass, NBR



C	F	H	K	L	Kg
G1/4 0627 00 13	19	43.5	20	40	0.097

Pressure: 10 bar


This isolating valve is used to connect a pressure gauge to a circuit.

Resetting the lever isolates and vents the gauge.

A locking pin can be used to enable the gauge to be fitted permanently.

## 0630 Pressure Relief Valve, Male BSP Thread

Brass



C	E	F	H	Kg
G1/4 0630 06 13	9	17	42.5	0.050


This valve is delivered without calibration, but can be adjusted by inserting metal washers into the hexagon (F).

Maximum working pressure: 10 bar

Calibration from 1 to 10 bar (not below)

## 0591 Needle Valve, Female BSP Thread

Stainless steel 316L, PTFE



DN	C	F	H min	H max	H1	L	L1	Kg
3	G1/8 0591 03 10	22	90	99	90	25	45	0.342
4	G1/4 0591 04 13	22	90	99	90	25	50	0.354
5	G3/8 0591 05 17	22	90	104	90	30	56	0.430
6	G1/2 0591 06 21	22	90	104	90	30	62	0.478

# Butterfly Valves



The butterfly valve allows frequent operation with very low torque on circuits without retention zones.

## Technical Characteristics

- **Compatible Fluids:** Compressed air, abrasive fluids
- **Working Pressure:** 0 to 16 bar
- **Working Temperature:** -20°C to +80°C


Reliable performance is dependent upon the type of fluid conveyed.

## Advantages

- Compatible with abrasive fluids (including solid particles)
- Fluid flow direction marked (uni-directional)
- Small size
- Simple and efficient design

## Component Materials

### Silicone-free




## Regulations

- PED
- REACH
- RoHS

## 4602 2/2 Butterfly Shut-Off Valve, Female BSPP Thread

Nickel-plated brass, NBR



DN	C		E	F	H	L	M	Kg
6	G1/4	4602 06 13	9	17	35	34	54	0.102
7	G3/8	4602 07 17	11	22	35	39	54	0.136
10	G1/2	4602 10 21	12	24	37	42	54	0.140
13	G3/4	4602 13 27	14	30	40	49	54	0.208
18	G1	4602 18 34	15	41	46	55	54	0.412

# Axial Valves



This valve is equipped with a pneumatic actuator. It can be controlled pneumatically or electro-pneumatically (using a NAMUR spool valve or solenoid valve) for integration into automated systems. Available with or without detection.

## Technical Characteristics

- **Compatible Fluids:** Compressed air, water, industrial fluids...  
Other fluids: please consult us
- **Working Pressure:** 10 bar max.
- **Pilot Pressure:** NC and NO: 4.2 to 8 bar  
Double-acting: 3 to 8 bar
- **Working Temperature:** -20°C to +150°C (EPDM and FKM)  
With detection: +90°C max


Reliable performance is dependent upon the type of fluid conveyed, component materials and tubing being used.

Guaranteed for use with a vacuum of 23 mm Hg (97% vacuum).

## Advantages

- Compact solution
- Easy to install: ready-to-use
- Two seal materials (FKM, EPDM) for a wider chemical and temperature range
- Pneumatic or electro-pneumatic
- Three versions: normally closed, normally open and double-acting
- Available with or without detection

## Pressure/Temperature




## Component Materials

### Silicone-free



## Flow Curve and Pressure Drop (Kv)

Kv in m³/h (ambient water temperature, under a differential pressure of 1 bar)




## Regulations

- PED
- RoHS
- REACH


## Operation

Depending on operational requirement, piloting air is passed into the actuation chamber to open or close the valve.


### Normally Closed Axial Valve (NC)



### Normally Open Axial Valve (NO)



### Double-Acting Axial Valve (DA)



## Installation Options

The Parker Legris axial valve offers 3 control methods depending on the application:

### Pneumatic Control

- available for single or double acting
- local compressed air control
- for repetitive on/off cycles
- remote control where access to the machine is difficult or ATEX areas



Pneumatic operation

### Electro-Pneumatic Control

with NAMUR spool valve (3/2 for single acting - 5/2 for double acting)

- available for single or double acting
- for automated industrial systems
- Namur pad-mounting (delivered unassembled)
- robust and compact solution
- better response time than other technologies



Electro-pneumatic operation

### Electro-Pneumatic Control

with solenoid valves (3/2)

- recommended for single acting
- for automated industrial systems
- pilot solenoid valve banjo G1/8 normally closed 3/2
- easy to connect
- swivel at 360°



Electro-pneumatic operation

## Product Codes

Valve type **42 XX 10 YY ZZ**

Without detection  
 4202: Normally closed  
 4212: Normally open  
 4222: Double acting

With detection  
 4204: Normally closed  
 4214: Normally open  
 4224: Double acting


Seals Material  
 20: FKM  
 30: EPDM  
 (only for NC version)

Pipe Size (inch):  
 17: Rp3/8"  
 21: Rp1/2"  
 27: Rp3/4"  
 34: Rp1"  
 42: Rp1 1/4"  
 49: Rp1 1/2"  
 48: Rp2"

10 = 10 mm  
 15 = 15 mm  
 20 = 20 mm  
 25 = 25 mm  
 32 = 32 mm  
 40 = 40 mm  
 50 = 50 mm

### 4202/4204..20 Normally Closed Axial Valve with FKM Seal, Female BSPP Thread

Nickel-plated brass, FKM




C	Without detection	With detection	F	G	H	H1	L	Kg
Rp3/8	4202 10 17 20	4204 10 17 20	22	46	53.5	30.5	98	0.650
Rp1/2	4202 15 21 20	4204 15 21 20	27	52	59	33	113	0.850
Rp3/4	4202 20 27 20	4204 20 27 20	33	63.5	71	39	136	1.500
Rp1	4202 25 34 20	4204 25 34 20	41	69	76	41.5	144	1.700
Rp1 1/4	4202 32 42 20*	4204 32 42 20*	50	86	91	48	166	3.300
Rp1 1/2	4202 40 49 20*	4204 40 49 20*	60	96	102	54	181	3.600
Rp2	4202 50 48 20*	4204 50 48 20*	70	109	115	60	205	5.100

Pilot port: G1/8  
 Delivered with a silencer  
 \*Models with EC marking  
 Threads conformed to ISO 7/1 (Rp)

### 4202/4204..30 Normally Closed Axial Valve with EPDM seal, Female BSPP Thread

Nickel-plated brass, EPDM




C	Without detection	With detection	F	G	H	H1	L	Kg
Rp3/8	4202 10 17 30	4204 10 17 30	22	46	53.5	30.5	98	0.650
Rp1/2	4202 15 21 30	4204 15 21 30	27	52	59	33	113	0.850
Rp3/4	4202 20 27 30	4204 20 27 30	33	63.5	71	39	136	1.500
Rp1	4202 25 34 30	4204 25 34 30	41	69	76	41.5	144	1.700
Rp1 1/4	4202 32 42 30*	4204 32 42 30*	50	86	91	48	166	3.300
Rp1 1/2	4202 40 49 30*	4204 40 49 30*	60	96	102	54	181	3.600
Rp2	4202 50 48 30*	4204 50 48 30*	70	109	115	60	205	5.100

Pilot port: G1/8  
 Delivered with a silencer  
 \*Models with EC marking  
 Threads conformed to ISO 7/1 (Rp)

## 4212/4214..20 Normally Open Axial Valve with FKM Seal, Female BSPP Thread

Nickel-plated brass, FKM




C	Without detection	With detection	F	G	H	H1	L	Kg
Rp3/8	4212 10 17 20	4214 10 17 20	22	46	53.5	30.5	98	0.650
Rp1/2	4212 15 21 20	4214 15 21 20	27	52	59	33	113	0.850
Rp3/4	4212 20 27 20	4214 20 27 20	33	63.5	71	39	136	1.500
Rp1	4212 25 34 20	4214 25 34 20	41	69	76	41.5	144	1.700
Rp1 1/4	4212 32 42 20*	4214 32 42 20*	50	86	91	48	166	3.300
Rp1 1/2	4212 40 49 20*	4214 40 49 20*	60	96	102	54	181	3.600
Rp2	4212 50 48 20*	4214 50 48 20*	70	109	115	60	205	5.100

Pilot port: G1/8  
 Delivered with a silencer  
 \*Models with EC marking  
 Threads conformed to ISO 7/1 (Rp)

## 4222/4224..20 Double-Acting Axial Valve with FKM Seal, Female BSPP Thread

Nickel-plated brass, FKM




C	Without detection	With detection	F	G	H	H1	L	Kg
Rp3/8	4222 10 17 20	4224 10 17 20	22	46	53.5	30.5	98	0.600
Rp1/2	4222 15 21 20	4224 15 21 20	27	52	59	33	113	0.800
Rp3/4	4222 20 27 20	4224 20 27 20	33	63.5	71	39	136	1.400
Rp1	4222 25 34 20	4224 25 34 20	41	69	76	41.5	144	1.600
Rp1 1/4	4222 32 42 20*	4224 32 42 20*	50	86	91	48	166	3.000
Rp1 1/2	4222 40 49 20*	4224 40 49 20*	60	96	102	54	181	3.300
Rp2	4222 50 48 20*	4224 50 48 20*	70	109	115	60	205	4.800

Pilot port: G1/8  
 \*Models with EC marking  
 Threads conformed to ISO 7/1 (Rp)

## Sub-Base for control with spool valve or solenoid valve with Namur pad mounting

Technical polymer



Delivered with the valve, unassembled

## 4243 Spare parts kit



Kit

4243 00 10 20	Kit for FKM seal DN10
4243 00 10 30	Kit for EPDM seal DN10
4243 00 15 20	Kit for FKM seal DN15
4243 00 15 30	Kit for EPDM seal DN15
4243 00 20 20	Kit for FKM seal DN20
4243 00 20 30	Kit for EPDM seal DN20
4243 00 25 20	Kit for FKM seal DN25
4243 00 25 30	Kit for EPDM seal DN25
4243 00 32 20	Kit for FKM seal DN32
4243 00 32 30	Kit for EPDM seal DN32
4243 00 40 20	Kit for FKM seal DN40
4243 00 40 30	Kit for EPDM seal DN40
4243 00 50 20	Kit for FKM seal DN50
4243 00 50 30	Kit for EPDM seal DN50

## 4298 00 02 Limit Switch


Nickel-plated brass, FKM



The valve is delivered with a magnet in the piston (assembled during the production) and supplied with a slot for mounting the limit switch(es). We provide separately inductive limit switch with LED which can be easily mounted in the slot and fixed with their screws.



- REED PNP, LED
- 3 wires (2 meters)
- Operating voltage 5-50 AC/DC
- Permanent current rating of switching output AC = 350 mA ; DC = 500 mA
- IP67, CE, UKCA, UL, EAC, CCC



- A = Body seal
- B = Piston seal
- C = Lip seals
- D = Stem seals
- E = Piston seal

## Complementary Range Products

### Namur Pilot Spool Valve

Parker Series 331 3/2  
 Parker Series 341 5/2



### Pilot Solenoid Valve G1/8" 3/2

Parker Series 131

