



Couplers - Brass, Steel, 303 Stainless - Female Thread



| Body Size | Part No. Brass | Weight (lbs.) | Part No. Steel | Weight (lbs.) | Part No. Type 303 Stainless** | Weight (lbs.) | Thread Size | Overall Length | Wrench Flats | Largest Dia |
|-----------|----------------|---------------|----------------|---------------|-------------------------------|---------------|-----------------|----------------|--------------|-------------|
| 1/8 | BH1-60 | 0.16 | H1-62 | 0.16 | SH1-62 | 0.16 | 1/8-27 NPTF | 1.90 | 0.68 | 0.96 |
| 1/8 | - | - | H1-62-T4 | 0.18 | SH1-62-T4 | 0.10 | 7/16-20 ORB | 2.06 | 0.68 | 0.96 |
| 1/4 | BH2-60 | 0.32 | H2-62 | 0.30 | SH2-62 | 0.30 | 1/4-18 NPTF | 2.26 | 0.81 | 1.14 |
| 1/4 | - | - | H2-62-T6 | 0.31 | SH2-62-T6 | 0.31 | 9/16-18 ORB | 2.41 | 0.81 | 1.14 |
| 3/8 | BH3-60 | 0.43 | H3-62 | 0.40 | SH3-62 | 0.40 | 3/8-18 NPTF | 2.49 | 0.88 | 1.40 |
| 3/8 | - | - | H3-62-T8 | 0.51 | SH3-62-T8 | 0.51 | 3/4-16 ORB | 2.75 | 1.00 | 1.40 |
| 1/2 | BH4-60 | 0.80 | H4-62 | 0.73 | SH4-62 | 0.75 | 1/2-14 NPTF | 2.87 | 1.12 | 1.77 |
| 1/2 | - | - | H4-62-T10 | 0.78 | SH4-62-T10 | 0.75 | 7/8-14 ORB | 3.05 | 1.12 | 1.77 |
| 3/4 | BH6-60 | 1.31 | H6-62 | 1.30 | SH6-62 | 1.31 | 3/4-14 NPTF | 3.56 | 1.31 | 2.14 |
| 3/4 | - | - | H6-62-T12 | 1.39 | SH6-62-T12 | 1.34 | 1-1/16 - 12 ORB | 3.56 | 1.31 | 2.14 |
| 1 | BH8-60 | 1.95 | H8-62 | 1.95 | SH8-62 | 1.95 | 1 - 11 1/2 NPTF | 4.18 | 1.62 | 2.52 |
| 1 | - | - | H8-62-T16 | 1.95 | SH8-62-T16 | 1.95 | 1-5/16 - 12 ORB | 4.18 | 1.62 | 2.52 |

Couplers - Brass, Steel, 303 Stainless - Female Thread



| Body Size | Part No. Brass | Weight (lbs.) | Part No. Steel | Weight (lbs.) | Part No. Type 303 Stainless** | Weight (lbs.) | Thread Size | Overall Length | Wrench Flats | Largest Dia |
|-----------|----------------|---------------|----------------|---------------|-------------------------------|---------------|---------------------|----------------|--------------|-------------|
| 1-1/2 | BH12-60L | 4.58 | H12-62L | 4.70 | SH12-62L | 4.68 | 1-1/4 - 11 1/2 NPTF | 4.86 | 2.38* | 3.00 |
| 1-1/2 | BH12-60N | 4.58 | H12-62N | 4.70 | SH12-62N | 4.68 | 1-1/2 - 11 1/2 NPTF | 4.86 | 2.38* | 3.00 |
| 1-1/2 | - | 4.61 | H12-62-T20 | 4.72 | SH12-62-T20 | 4.71 | 1-5/8 - 12 ORB | 4.86 | 2.38* | 3.00 |
| 1-1/2 | - | 4.61 | H12-62-T24 | 4.72 | SH12-62-T24 | 4.71 | 1-7/8 - 12 ORB | 4.86 | 2.38* | 3.00 |
| 2-1/2 | BH2016-60 | 11.06 | H2016-62 | 10.58 | SH2016-62 | - | 2 - 11 1/2 NPTF | 5.57 | 3.75 | 4.10 |
| 2-1/2 | BH2020-60 | 11.42 | H2020-62 | 10.91 | SH2020-62 | - | 2 1/2 - 8 NPTF | 6.04 | 3.75 | 4.10 |
| 2-1/2 | BH2024-60 | - | H2024-62 | - | SH2024-62 | - | 3 - 8 NPTF | 6.69 | 4.00 | 4.35 |


* Wrench Flat on 303 Stainless is 2.50 in.

** Prop 65 Warning does not apply to stainless steel part numbers

WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Couplers and Nipples - 316 Stainless - Female Thread



| Body Size | Coupler Part No. Type 316 Stainless** | Weight (lbs.) | Thread Size | Overall Length | Wrench Flats | Largest Dia | Nipple Part No. Type 316 Stainless** | Weight (lbs.) | Overall Length | Exposed Length* | Wrench Flats | Largest Dia |
|-----------|---------------------------------------|---------------|--------------------|----------------|--------------|-------------|--------------------------------------|---------------|----------------|-----------------|--------------|-------------|
| 1/8 | SSH1-62Y | 0.15 | 1/8-27 NPT | 1.90 | 0.68 | 0.96 | SSH1-63Y | 0.04 | 1.26 | 0.44 | 0.56 | 0.65 |
| 1/8 | SSH1-62Y-T4 | 0.17 | 7/16-20 ORB | 2.06 | 0.68 | 0.96 | SSH1-63Y-T4 | 0.06 | 1.41 | 0.59 | 0.69 | 0.78 |
| 1/4 | SSH2-62Y | 0.30 | 1/4-18 NPT | 2.26 | 0.81 | 1.14 | SSH2-63Y | 0.08 | 1.54 | 0.55 | 0.75 | 0.87 |
| 1/4 | SSH2-62Y-T6 | 0.31 | 9/16-18 ORB | 2.41 | 0.81 | 1.14 | SSH2-63Y-T6 | 0.10 | 1.69 | 0.70 | 0.88 | 1.01 |
| 3/8 | SSH3-62Y | 0.40 | 3/8-18 NPT | 2.49 | 0.88 | 1.40 | SSH3-63Y | 0.12 | 1.68 | 0.54 | 0.88 | 1.01 |
| 3/8 | SSH3-62Y-T8 | 0.51 | 3/4-16 ORB | 2.75 | 1.00 | 1.40 | SSH3-63Y-T8 | 0.14 | 1.94 | 0.80 | 1.00 | 1.15 |
| 1/2 | SSH4-62Y | 0.76 | 1/2-14 NPT | 2.87 | 1.12 | 1.77 | SSH4-63Y | 0.24 | 1.94 | 0.69 | 1.12 | 1.30 |
| 1/2 | SSH4-62Y-T10 | 0.78 | 7/8-14 ORB | 3.05 | 1.12 | 1.77 | SSH4-63Y-T10 | 0.27 | 2.12 | 0.87 | 1.19 | 1.37 |
| 3/4 | SSH6-62Y | 1.33 | 3/4-14 NPT | 3.56 | 1.31 | 2.14 | SSH6-63Y | 0.46 | 2.43 | 0.79 | 1.38 | 1.59 |
| 3/4 | SSH6-62Y-T12 | 1.40 | 1-1/16 - 12 ORB | 3.56 | 1.31 | 2.14 | SSH6-63Y-T12 | 0.50 | 2.54 | 0.90 | 1.34 | 1.59 |
| 1 | SSH8-62Y | 1.95 | 1 - 11 1/2 NPT | 4.18 | 1.62 | 2.52 | SSH8-63Y | 0.76 | 2.91 | 0.99 | 1.62 | 1.88 |
| 1 | SSH8-62Y-T16 | 1.95 | 1-5/16 - 12 ORB | 4.18 | 1.62 | 2.52 | SSH8-63Y-T16 | 0.80 | 2.91 | 0.99 | 1.62 | 1.88 |
| 1-1/2 | SSH12-62LY | 4.68 | 1-1/4 - 11 1/2 NPT | 4.86 | 2.38 | 3.00 | SSH12-63LY | - | 4.76 | 2.69 | 2.38 | 2.75 |
| 1-1/2 | SSH12-62NY | 4.68 | 1-1/2 - 11 1/2 NPT | 4.86 | 2.38 | 3.00 | SSH12-63NY | - | 4.76 | 2.69 | 2.38 | 2.75 |
| 1-1/2 | SSH12-62Y-T20 | 4.71 | 1-5/8 - 12 ORB | 4.86 | 2.38 | 3.00 | SSH12-63Y-T20 | - | 4.76 | 2.69 | 2.38 | 2.75 |
| 1-1/2 | SSH12-62Y-T24 | 4.71 | 1-7/8 - 12 ORB | 4.86 | 2.38 | 3.00 | SSH12-63Y-T24 | - | 4.76 | 2.69 | 2.38 | 2.75 |
| 2-1/2 | SSH2016-62Y | - | 2 - 11 1/2 NPT | 5.57 | 3.75 | 4.10 | SSH2016-63Y | - | 5.48 | 2.90 | 3.75 | 4.10 |
| 2-1/2 | SSH2020-62Y | - | 2 1/2 - 8 NPT | 6.04 | 3.75 | 4.10 | SSH2020-63Y | - | 5.95 | 3.37 | 3.75 | 4.10 |
| 2-1/2 | SSH2024-62Y | - | 3 - 8 NPT | 6.69 | 4.00 | 4.35 | SSH2024-63Y | - | 6.87 | 4.29 | 4.00 | 4.35 |

* This dimension represents the portion that is exposed when the nipple is inserted into the mating Parker Coupler.

** Prop 65 Warning does not apply to stainless steel part numbers



Nipples - Brass, Steel, 303 Stainless - Female Thread



| Body Size | Part No. Brass | Weight (lbs.) | Part No. Steel | Weight (lbs.) | Part No. Type 303 Stainless** | Weight (lbs.) | Thread Size | Overall Length | Exposed Length* | Wrench Flats | Largest Dia |
|-----------|----------------|---------------|----------------|---------------|-------------------------------|---------------|-----------------|----------------|-----------------|--------------|-------------|
| 1/8 | BH1-61 | 0.04 | H1-63 | 0.03 | SH1-63 | 0.03 | 1/8-27 NPTF | 1.26 | 0.44 | 0.56 | 0.65 |
| 1/8 | - | 0.06 | H1-63-T4 | 0.05 | SH1-63-T4 | - | 7/16-20 ORB | 1.41 | 0.59 | 0.69 | 0.78 |
| 1/4 | BH2-61 | 0.09 | H2-63 | 0.08 | SH2-63 | 0.08 | 1/4-18 NPTF | 1.54 | 0.55 | 0.75 | 0.87 |
| 1/4 | - | 0.11 | H2-63-T6 | 0.10 | SH2-63-T6 | 0.10 | 9/16-18 ORB | 1.69 | 0.70 | 0.88 | 1.01 |
| 3/8 | BH3-61 | 0.10 | H3-63 | 0.12 | SH3-63 | 0.12 | 3/8-18 NPTF | 1.68 | 0.54 | 0.88 | 1.01 |
| 3/8 | - | 0.12 | H3-63-T8 | 0.16 | SH3-63-T8 | 0.16 | 3/4-16 ORB | 1.94 | 0.80 | 1.00 | 1.15 |
| 1/2 | BH4-61 | 0.25 | H4-63 | 0.24 | SH4-63 | 0.24 | 1/2-14 NPTF | 1.94 | 0.69 | 1.12 | 1.30 |
| 1/2 | - | 0.28 | H4-63-T10 | 0.27 | SH4-63-T10 | 0.27 | 7/8-14 ORB | 2.12 | 0.87 | 1.19 | 1.37 |
| 3/4 | BH6-61 | 0.50 | H6-63 | 0.46 | SH6-63 | 0.45 | 3/4-14 NPTF | 2.43 | 0.79 | 1.38 | 1.59 |
| 3/4 | - | 0.55 | H6-63-T12 | 0.46 | SH6-63-T12 | 0.50 | 1-1/16 - 12 ORB | 2.54 | 0.90 | 1.34 | 1.59 |
| 1 | BH8-61 | 0.76 | H8-63 | 0.76 | SH8-63 | 0.76 | 1 - 11 1/2 NPTF | 2.91 | 0.99 | 1.62 | 1.88 |
| 1 | - | 0.80 | H8-63-T16 | 0.80 | SH8-63-T16 | 0.80 | 1-5/16 - 12 ORB | 2.91 | 0.99 | 1.62 | 1.88 |

* This dimension represents the portion that is exposed when the nipple is inserted into the mating Parker Coupler.

Nipples - Brass, Steel, 303 Stainless - Female Thread



| Body Size | Part No. Brass | Weight (lbs.) | Part No. Steel | Weight (lbs.) | Part No. Type 303 Stainless** | Weight (lbs.) | Thread Size | Overall Length | Exposed Length* | Wrench Flats | Largest Dia |
|-----------|----------------|---------------|----------------|---------------|-------------------------------|---------------|---------------------|----------------|-----------------|--------------|-------------|
| 1-1/2 | BH12-61L | 2.96 | H12-63L | 3.10 | SH12-63L | 3.06 | 1-1/4 - 11 1/2 NPTF | 4.76 | 2.69 | 2.38‡ | 2.75† |
| 1-1/2 | BH12-61N | 2.96 | H12-63N | 3.10 | SH12-63N | 3.06 | 1-1/2 - 11 1/2 NPTF | 4.76 | 2.69 | 2.38‡ | 2.75† |
| 1-1/2 | - | - | H12-63-T20 | 3.15 | SH12-63-T20 | 3.14 | 1-5/8 - 12 ORB | 4.76 | 2.69 | 2.38‡ | 2.75† |
| 1-1/2 | - | - | H12-63-T24 | 3.15 | SH12-63-T24 | 3.14 | 1-7/8 - 12 ORB | 4.76 | 2.69 | 2.38‡ | 2.75† |
| 2-1/2 | BH2016-61 | 7.78 | H2016-63 | 7.90 | SH2016-63 | 7.92 | 2 - 11 1/2 NPTF | 5.48 | 2.90 | 3.75 | 4.10 |
| 2-1/2 | BH2020-61 | 8.12 | H2020-63 | 8.16 | SH2020-63 | 8.16 | 2-1/2 - 8 NPTF | 5.95 | 3.37 | 3.75 | 4.10 |
| 2-1/2 | BH2024-61 | - | H2024-63 | - | SH2024-63 | - | 3 - 8 NPTF | 6.87 | 4.29 | 4.00 | 4.35 |

* This dimension represents the portion that is exposed when the nipple is inserted into the mating Parker Coupler.

† Largest diameter on Brass is 2.96" across Hex Corners

‡ Hex on 303 Stainless is 2.50 in.

** Prop 65 Warning does not apply to stainless steel part numbers



WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov